

Give your teams the tools, technologies and colour capabilities they need to be more creative, collaborative and productive.

Intelligent multifunction devices built for your modern office and workstyle.

Business is taking place beyond the physical office. To be successful, companies need versatile technology that reflects new ways of working and collaborating. Our latest series of colour multifunction devices reflect that change — offering an array of impressive features to help your entire organization be more efficient and productive.

- Print, copy, scan and fax (optional)
- Output speeds up to 35 ppm
- Eco-friendly, compact design
- Tablet-like Smart Operation Panel
- Mobile connectivity options
- Automatic firmware updates
- · Built-in security features
- Outstanding support and uptime
- Seamless cloud connectivity options
- Optional finishing solutions



RICOH IM C3010/IM C3510 main specifications

General

| Contrai | |
|---|--|
| Warm-up time | 25 seconds |
| First output speed | IM C3010: B&W: 4.0 seconds, Colour: 6.6 seconds |
| · · | IM C3510: B&W: 4.0 seconds, Colour: 6.6 seconds |
| Continuous output speed | IM C3010: 30 ppm |
| | IM C3510: 35 ppm |
| Memory: standard/maximum | 4 GB (mainframe) |
| | 4 GB (Smart Operation Panel) |
| Solid State Drive (SSD): standard/maximum | 256 GB |
| Single-Pass Document Feeder | 220 sheets |
| (SPDF) capacity | |
| Weight | 218.9 lbs./99.3 kg |
| Dimensions: | 23.1" × 27.6" × 37.9" |
| W × D × H | (587 × 701 × 963 mm) |
| Power source | 120V – 127V 60Hz |
| Copier (standard) | |
| Multiple copying | Up to 999 copies |
| Resolution | 600 dpi |
| Zoom | From 25% to 400% in 1% steps |
| 20011 | |
| Printer (standard) | |
| CPU | Intel Apollo Lake 1.3GHz |
| Printer language: standard | PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation) |
| Printer language: option | Genuine Adobe [®] PostScript [®] 3 [™] , PDF Direct from Adobe [®] , IPDS |
| Print resolution | Up to 1200 × 1200 dpi |
| Network interface: standard | Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B |
| Network interface: option | Wireless LAN (IEEE 802.11a/b/g/n/ac) |
| Mobile printing capability | Apple AirPrint [®] , Mopria [®] , RICOH Smart Device Connector |
| Windows [®] environments | Windows [®] 8.1, Windows [®] 10, Windows [®] Server 2012R2, Windows [®] Server 2016, |
| | Windows [®] Server 2019, Windows [®] Server 2022 |
| Mac OS environments | Macintosh OS X v10.15 or later |
| UNIX environments | UNIX Sun [®] Solaris, HP-UX, SCO OpenServer, RedHat [®] Linux Enterprise, IBM [®] AIX |
| SAP [®] environments | SAP® R/3 [®] , S/4 [®] |
| Other supported environments | IBM iSeries AS/400 using OS/400 Host Print Transform |
| Scanner (standard) | |
| Speed | 150 ipm (simplex) 300 ipm (duplex) |
| Resolution: maximum | Up to 1200 dpi (A5 or smaller paper size) |
| Compression method | B&W: JBIG2/MH/MMR/MR Colouur: JPEG |
| File formats | Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, Encrypted PDF, Searchable PDF |

Multi Page: TIFF, PDF (Default), High Compression PDF, Encrypted PDF, Searchable PDF*

*Requires optional OCR Unit Type M52.

E-mail, Folder, USB, URL, FTP

Scan modes

| Facsimile (optional) | |
|----------------------------|---|
| Circuit | PSTN, PBX |
| Transmission speed | 3 seconds (200 × 100 dpi, JBIG, ITU-T (CCITT) test chart #1, memory transmission) |
| Modem speed: maximum | 33.6 Kbps |
| Resolution: standard | 8 × 3.85 line/mm, 200 × 100 dpi |
| Maximum resolution: option | 16 × 15.4 line/mm, 400 × 400 dpi |
| Compression method | MH, MR, MMR, JBIG |
| Scanning speed | Up to 94 ppm A4/LT, SEF, standard resolution |
| Memory: standard | 4 MB (320 pages) |
| Memory: maximum | 60 MB (4,800 pages) |

Paper handling

| i aper nanaling | |
|--|---|
| Recommended paper sizes | Tray 1: 8.5" × 11" (A4) Tray 2: 5.5" × 8.5" – 12" × 18" (A3 – A6, B4 – B6), Envelopes Bypass Tray: Up to 12" × 18", Envelopes, Custom Sizes [Width: 3.5" – 12.6" (90 – 320 mm), Length: 5.8" – 49.6" (148 – 1,260 mm)] |
| Paper input: standard | 1,200 sheets |
| Paper input: maximum | 4,850 sheets |
| Paper output: standard | 500 sheets 8.5" × 11" (A4) or smaller; 250 sheets (B4) or larger |
| Paper output: maximum | 1,625 sheets |
| Paper weight | Trays: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²) Bypass Tray: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²) Duplex: 14 – 68 lb./142 lb. Index (52 – 256 g/m ²) |
| 2 × 550-sheet Paper Tray (PB3320) option | Paper size: 5.5"× 8.5" to 12"× 18" (A6 – A3), Paper weight: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²) |
| 1,650-sheet Side Large Capacity Tray (LCIT RT3050) option | Paper size: 8.5" × 11" (A4, B5), Paper weight: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²) n |
| 2,000-sheet Large Capacity Tray (LCIT PB3330) option | Paper size: 8.5"× 11" (A4), Paper weight: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²) |
| Paper types | Plain, Recycled, Special, Coloured, Letterhead, Cardstock, Pre-printed, Coated, Envelope, Label, Gloss |
| | |

Environmental features

| Power consumption: maximum | Less than 1,584 W |
|------------------------------|---|
| Power consumption: operation | IM C3010: B&W: 473 W, Colour: 522 W |
| | IM C3510: B&W: 488 W, Colour: 548 W |
| Power consumption | Ready: 46.2 W |
| | Sleep: 0.3 W |
| TEC ¹ | IM C3010: 0.30 kWh |
| | IM C3510: 0.35 kWh |
| ENERGY STAR [®] | Certified |
| EPEAT [®] | Gold Rated* |
| | *EPEAT Gold rating is applicable only in the USA. |

¹TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

- Some options may not be available at the time of market release.

- Specifications are subject to change without notice.
- For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.
- Some features may require additional options and/or charges.

Output trays and finishing options

| Internal Multi-fold Unit (FD3020) | Z folding: A3, B4, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio), 12" × 18" Inner/Outer three-folding: A3, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio) Paper weights for folding: Single Sheet mode: 17 – 28 lb./58 lb. Index (64 – 105 g/m ²), Multiple Sheet mode (three-fold only): 17 – 21 lb./44 lb. Index (64 – 80 g/m ²) |
|--|---|
| Internal Shift Tray (SH3090) | Tray capacity: 250 sheets with 80 g/m ² paper (A4, LT or smaller), 125 sheets with 80 g/m ² paper (B4, LG or larger); Paper size: 12.60" × 23.62" or smaller; Paper weight: $14 - 80$ lb./166 lb. Index (52 - 300 g/m ²) |
| One-bin Tray (BN3140) | Tray capacity: 125 sheets, Paper size: 5.5"× 8.5" to 12"×18" (A5 – A3); Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m²) |
| 500-sheet Internal Finisher (SR3310) | Paper size: $5.5" \times 8.5"$ to $12" \times 18"$ (A6 – A3); Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²); Staple capacity: 50 sheets ($8.5" \times 11"$) (A4), 30 sheets ($8.5" \times 14"$ or larger, and/or Mixed Sizes) (B4 – A3); Staple paper size: $7.25" \times 10.5"$ to $11" \times 17"$ (B5 – A3); Staple paper weight: 14 – 28 lb. (52 – 105 g/m ²); Staple positions: Top, Bottom, 2 staples |
| 1,000-sheet Hybrid Finisher (SR3320) | Paper size: Proof Tray: $5.5" \times 8.5"$ to $12" \times 18"$ (A6 – A3); Shift Tray: $5.5" \times 8.5"$ to $12" \times 18"$ (A6 – A3), Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²), Staple capacity: 50 sheets; Staple paper size: $8.5" \times 11"$ to $12" \times 18"$ (A4 – A3); Staple paper weight: 14 – 28 lb. (52 – 105 g/m ²); Staple positions: Top, Bottom, 2 staples |
| 1,000-sheet Booklet Finisher (SR3330) | Paper size: Proof Tray: $5.5" \times 8.5"$ to $12" \times 18"$ (A6 – A3); Shift Tray: $5.5" \times 8.5"$ to $12" \times 18"$ (A6 – A3); Booklet Tray: $8.5" \times 11"$ to $12" \times 18"$ (A4 – A3); Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²); Staple capacity: 50 sheets ($8.5" \times 11"$) (A4), 30 sheets ($8.5" \times 14"$ or larger, and/or Mixed Sizes) (B4 – A3); Staple paper size: Normal Staple: $8.5" \times 11"$ to $12 \times 18"$ (A4 – A3); Saddle Stitch: $8.5" \times 11"$ to $12" \times 18"$ (A4 – A3); Staple paper weight: 14 – 28 lb. (52 – 105 g/m ²); Staple positions: Top, Bottom, 2 staples, Booklet |

Other options

Adobe[®] PostScript[®] 3[™] Unit Type M52, Bridge Unit BU3100, Cabinet Type A5, Card Reader Cover Type M52, Enhanced Security SSD Option Type M52 256GB, Fax Memory Unit Type M52, Fax Option Type M52, G3 Interface Unit Type M52, HDD Option Type M52 320GB, IEEE 802.11a/b/g/n/ac Interface Unit Type M52, IPDS Unit Type M52,OCR Unit Type M52, Optional Counter Interface Unit Type M12, Power Filter, Punch units (PU3100, PU3080), Unicode Font Package for SAP[®] 1 License, Color Controller E-26C, Fiery Impose, Fiery ColorRight Package, Fiery Automation Package, Fiery Color Profiler Suite, ES-3000 spectrophotometer, Fiery ColorGuard, IQ Manage, Fiery JobFlow

| Consumables | |
|---|---------------|
| Toner: black | 31,000 prints |
| Toner: cyan/magenta/yellow | 19,000 prints |
| Consumption violate based on 2 pages/ich and EV/ severage on A4 paper | |

Consumable yields based on 3 pages/job and 5% coverage on A4 paper



To learn about these intelligent devices, visit **ricoh.ca** or speak with your Ricoh specialist today.



Ricoh Canada Inc., 100-5560 Explorer Drive, Mississauga, ON L4W 5M3, 1-888-742-6417

©2024. Ricoh Canada Inc. All rights reserved. Ricoh and the Ricoh logo® are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.