

**B&W** multifunction printers

# IM 370F IM 460F **IM 460FTL**

Printer Copier Scanner Fax



# Versatile devices for dynamic office environments

Today, many organizations are seeking new ways to optimize office space and resources to accommodate changing work styles. Additionally, there is a rising need for a reliable IT and print infrastructure as organizations seek to seamlessly facilitate digital workflows and address security challenges.

This change has created an opportunity for cost-effective and robust workplace technology that streamlines operations, offers the flexibility to easily transition between paper and digital workflows, and provides enhanced data security.

Ricoh's latest generation of black-and-white multifunction devices optimizes day-to-day operations by enhancing productivity, increasing data security, and creating a seamless user experience in a compact all-in-one device.

Experience the versatility of the new IM 370F/IM 460F/IM 460FTL series — a perfect addition to today's modern workplace that empowers your teams to easily capture, print, share information, and digitize workflows.



Work more efficiently with fast black-and-white print and color scan speeds



Optimize office space with a compact multifunction device



Protect your business data and intellectual property



Customize options to match your workflow needs with RICOH Smart Integration technology



# A comprehensive solution for diverse workflow needs

# Enhanced quality, performance, and productivity

Experience the benefits of fast black-and-white print and color scan speeds with our compact letter/legal multifunction device. Enjoy the added convenience of A3 capabilities, allowing you to easily print, copy, and scan 11" x 17" pages when needed. What's more, you can personalize and enhance the capabilities of your device with applications and software solutions readily available from the cloud with RICOH Smart Integration.

## Improved usability and reliability

Ideal for smaller office workspaces or desktop environments, these devices offer space-saving efficiency and low noise levels. Ricoh's familiar, user-friendly Smart Operation Panel has been enhanced to provide a more intuitive and seamless user experience with an upgraded OS for better security and usability, as well as improved touch response and faster performance.

## Reliable protection of your data

Equipped with the latest controller features, these smart devices provide enhanced privileged account control that gives you more freedom when creating administrator roles and minimizes risks related to sharing IDs. You can also assign different privileges to each role and link it to your user ID system, including Windows and LDAP platforms. Additionally, Ricoh's Always Current Technology ensures automatic security and software updates downloaded and installed directly to your device as they become available.



### Enhanced sustainability features

As a leader in environmentally-friendly performance, we not only uphold our own commitments but also strive to help support your goals. Our devices utilize up to 17% post-consumer recycled materials for their outer mainframe, while toner bottles are made from 81% recycled plastics. There is zero plastic usage for the toner packaging and the device's optional paper feed unit. The Smart Operation Panel includes new energy-saving features to reduce the operation panel's power consumption by 45% in Sleep Mode.

# Specialized printing capabilities (IM 460FTL only)

Designed with the unique needs of healthcare professionals in mind, the IM 460FTL incorporates specialized firmware and Teflon-coated tray components to reliably print specialized media such as wristbands and labels. It also features a built-in locking tray and optional additional locking trays to safeguard sensitive media such as prescription blanks and more. Non-locking trays are also available for standard media printing.







## IM 370F/IM 460F/IM 460FTL

MAIN SPECIFICATIONS

GENERAL	IM 370F	IM 460F	IM 460FTL	
Warm-up time		Less than 32 seconds		
First copy speed: B/W		Less than 5 seconds		
First print speed: B/W	3.8 seconds	3.3 seconds	3.3 seconds	
Continuous output speed	37 ppm	46 ppm	46 ppm	
Nemory: standard	or ppm	6GB (Mainframe 2GB+SOP 4GB)	io pp.ii	
Optional Storage	Opt. 256 GB SSD or Opt. 320 GB HDD			
SPDF capacity	50 sheets			
Veight	41 kg / 90.4 lbs.			
Dimensions: W x D x H	•			
Power source	14.7"×19.4"×25.2" 120-127V 60Hz			
-ower source		120-127 0002		
COPIER				
Aultiple copying		Up to 999 copies		
Resolution	600 x 600 dpi			
Zoom	From 25%-400% in 1% increments			
PRINTER				
CPU		Marvell 88PA6270 1.2GHz		
Printer language: standard	PCL 5e, PCL6, PostScript®3™ Emulation, PDF Direct Print Emulation			
Printer language: option	Genuine Adobe® PostScript®3™, Adobe® PDF Direct Print, XPS, IPDS			
Print resolution: maximum	Up to 1200 x 1200 dpi			
letwork interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B			
Nobile printing capability	Apple AirPrint <sup>™</sup> , Mopria, Ricoh Smart Device Connector			
Vindows® environments	Windows 8.1/10/11; Windows Server 2016/2019/2022			
lac OS environments	v10.15 or later			
JNIX environments	UNIX Sun Solaris, HP-UX, SCO OpenServer, RedHat Linux Enterprise, IBM AIX			
SAP® environments	SAP R/3, SAP S/4			
SCANNER				
Scanning speed: SPDF		46 ipm (simplex)/92 ipm (duplex)		
Resolution: maximum		Up to 1200dpi		
Compression method File	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encrypted PDF, Searchable PDF (OCR Option required)			
Formats Scan destination types	Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encrypted PDF, Searchable PDF (OCR Option required) E-mail, Folder, USB, URL, FTP			
FAX (Optional)				
Circuit		PSTN, PBX		
Circuit ransmission speed		3 seconds		
Circuit Transmission speed Aodem speed: maximum		3 seconds 33.6 Kbps		
Circuit ransmission speed Addem speed: maximum Resolution: standard		3 seconds 33.6 Kbps 8x3.85 line/mm, 200x100 dpi		
Circuit Circui		3 seconds 33.6 Kbps 8x3.85 line/mm, 200x100 dpi 16x15.4 line/mm, 400x400 dpi		
Circuit Circui		3 seconds 33.6 Kbps 8x3.85 line/mm, 200x100 dpi 16x15.4 line/mm, 400x400 dpi MH, MR, MMR		
Circuit Circui		3 seconds 33.6 Kbps 8x3.85 line/mm, 200x100 dpi 16x15.4 line/mm, 400x400 dpi MH, MR, MMR 46 spm		
Circuit Circui		3 seconds 33.6 Kbps 8x3.85 line'mm, 200x100 dpi 16x15.4 line'mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages)		
Circuit Circui		3 seconds 33.6 Kbps 8x3.85 line/mm, 200x100 dpi 16x15.4 line/mm, 400x400 dpi MH, MR, MMR 46 spm		
Circuit Iransmission speed Modem speed: maximum Resolution: standard Maximum Resolution: option Compression method Scanning speed Memory: standard Memory: maximum PAPER HANDLING		3 seconds 33.6 Kbps 8x3.85 line/mm, 200x100 dpi 16x15.4 line/mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages) 60 MB, (4,800 pages)		
Circuit Transmission speed Modem speed: maximum Resolution: standard Maximum Resolution: option Compression method Scanning speed Memory: standard Memory: maximum PAPER HANDLING		3 seconds 33.6 Kbps 8x3.85 line'mm, 200x100 dpi 16x15.4 line'mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages)		
Circuit Transmission speed Addem speed: maximum Resolution: standard Aaximum Resolution: option Compression method Compression method Compression method Compression method Adamony: standard Adamony: standard Adamony: maximum PAPER HANDLING Recommended paper size		3 seconds 33.6 Kbps 8x3.85 line'mm, 200x100 dpi 16x15.4 line'mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages) 60 MB, (4,800 pages) Paper Tray: 4" x 6" - 8.5" x 11" (A4 - A6)		
Circuit Circuit Circuit Circuit Circuit Circuit Circuits		3 seconds 33.6 Kbps 8x3.85 line'mm, 200x100 dpi 16x15.4 line'mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages) 60 MB, (4,800 pages) Paper Tray: 4" x 6" - 8.5" x 11" (A4 - A6) Bypass: Up to 11.69" x 35", Envelopes		
Circuit Transmission speed Addem speed: maximum Resolution: standard Adaximum Resolution: option Compression method Scanning speed Ademory: standard Ademory: standard Ademory: maximum Compression Recommended paper size Paper input: standard Compression Recommended Paper size Pape		3 seconds 33.6 Kbps 8x3.85 line'mm, 200x100 dpi 16x15.4 line'mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages) 60 MB, (4,800 pages) Paper Tray: 4" x 6" - 8.5" x 11" (A4 - A6) Bypass: Up to 11.69" x 35", Envelopes 500-sheet tray, plus 100-sheet bypass	A4)	
Circuit Transmission speed Modem speed: maximum Resolution: standard Maximum Resolution: option Compression method Scanning speed Memory: standard Memory: maximum PAPER HANDLING Recommended paper size Paper input: standard Paper input: maximum		3 seconds 33.6 Kbps 8x3.85 line'mm, 200x100 dpi 16x15.4 line'mm, 400x400 dpi MH, MR, MMR 46 spm 4 MB, (320 pages) 60 MB, (4,800 pages) Paper Tray: 4" x 6" - 8.5" x 11" (A4 - A6) Bypass: Up to 11.69" x 35", Envelopes 500-sheet tray, plus 100-sheet bypass 2,100 sheets	A4)	

### IM 370F/IM 460F/IM 460FTL

MAIN SPECIFICATIONS

	IM 370F	IM 460F	IM 460FTL		
ENVIRONMENTAL FEATURES					
Power consumption: maximum		Less than 1600W			
Power consumption operation: B&W	527.6W	624.5W	624.5W		
Power consumption: ready / sleep		42.1W / 0.41W			
TEC*	0.38kWh	0.46kWh	0.46kWh		
Environmental Certifications		ENERGY STAR® Certified; EPEAT® Gold Rated**			
* TEC value is measured based on the ENERGY STAR Ver. 3.0 test method. ** EPEAT Gold rating is applicable only in the USA.					
CONSUMABLES					
Toner (black)	Standard-yield toner: 13,500 pages; High-yield toner (IM 460F/460FTL only): 22,000 pages				

Waste Toner Bottle

Yield: 50,000 pages

Declared toner yield in accordance with ISO/IEC 19752; Waste toner bottle yield based on 3 pages/job and 6% coverage on 8.5"x11" paper.

#### PAPER SUPPLY OPTIONS

Paper Feed Unit PB1200 (500 Sheet), Paper Feed Unit PB1200TL (500 Sheet Lock & Label), Medium Cabinet Type A7, High Cabinet Type A8, Caster Table Type A6

#### OTHER OPTIONS

Document Feeder Paper Guide Tray, HDD Option Type M54 320GB, SSD Option Type M54 256GB, IEEE 802.11a/b/g/n Interface Unit Type M54, PostScript3 Unit Type M54, OCR Unit Type M54, Fax Memory Unit Type M54 64MB, IPDS Unit Type M54, Optional Counter Interface Unit Type M12, Optional Card Reader Cover Type M54

This device does not support PoE (Power over Ethernet) and should not be connected to a PoE hub.

Connecting to a PoE hub could cause damage and void warranty coverage.

Some options may not be available at the time of market release.


Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Some features may require additional options and/or charges.







#### Ricoh USA, Inc., 300 Eagleview Blvd, Exton, PA 19341, 1-800-63-RICOH.

©2023 Ricoh USA, Inc. All rights reserved. Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks (22/22) Kicoh USA, linc. All rights reserved. Kicoh and the Kicoh logo are registered trademarks of Kicoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products are set forth in the express warranty statements accompanying them.