Color Sheet-fed Digital Press

RICOH Pro C9500





Enhance revenue, reduce operational costs and open doors to new applications.

Discover the RICOH Pro C9500 — a next-generation press for the next evolution of your business

If ever there was a digital color press tailor-made for the realities of our time yet also equipped to support the growth and potential of what lies ahead, the RICOH Pro C9500 is it. Building on a proven foundation, this new top-of-the-line system takes success to the next level with advanced technologies that drive automation and help you deliver high-quality, predictable results.

- Turbocharge productivity with a robust print controller designed for ease-ofuse and automation
- Expand offerings with media support from 40 – 470 gsm and oversized options
- Realize consistent color and quality with built-in advanced technologies

- Minimize waste and improve customer satisfaction with precise front-to-back registration
- Increase your capacity with monthly volumes of up to 1,000,000 pages
- Reduce operator intervention with auto duplex/perfecting up to 400 gsm













Scalable, affordable and highly intelligent

The RICOH Pro C9500 addresses the most pressing challenges facing commercial printers, print service providers and in-plants. These challenges include how to overcome labor shortages and appeal to a new generation of press operators, how to evolve from offset to digital without compromise, how to achieve exceptional color quality even in the most demanding production environments, and how to grow into high-margin segments (including packaging and signage) and drive profitability despite shorter runs.

Relentless performance for remarkable results

You need tough and innovative presses to get the job done and help you expand into new applications and markets. The RICOH Pro C9500 goes the distance and never lets up. Benefit from superior speeds of up to 135 pages per minute*, the ability to replace paper and toner while in operation, an 18,100-sheet maximum paper capacity and Trained Customer Replaceable Units (TCRU) that empower your business to perform preventive maintenance without waiting on a technician.



Work smarter from end-to-end

Predictable and repeatable results from the first page to the last.

Utilize the Fiery® N-50 Controller Digital Front End for light production and repetitive jobs or the new Fiery N-70® Controller Digital Front End to process larger and more complex files faster than ever.



- 3,500-Sheet Booklet & Staple Finisher (SR5120)*
 Saddle-stitch booklets up to 30 sheets and staple up to 100 sheets quickly at sizes up to 13" × 19.2".
- Plockmatic Booklet Maker PBM 5035/5035S*°
 Create booklets up to 50 sheets of paper inline or off-line with three-sided trimming and square fold. Supports up to 350 gsm coated or uncoated paper stocks.
- High-Capacity Stacker (SK5040)*

 A 5,000 sheet stacker with a rollaway cart quickly moves large output volumes to offline binding or packing and shipping.
- Perfect Binder (GB5010)*°
 Glue and bind up to 200 sheets with three-edge trimming, including covers up to 300 gsm.
- Six-Position Multi-Folding Unit (FD5030)*°
 Execute up to six types of folds to give your customers a wider range of finished documents.

GBC StreamPunch™ Plus & StreamWire*°

Achieve professional quality with inline punching for media up to 300 gsm. Automate inline binding systems when creating twin-loop wire-bound booklets.

- Full-Color Touch Screen Control Panel
 Transition between jobs effortlessly via
 fingertip control and animated guides from the
 post-mounted 21.5" LCD.
- Status Light Pole

 Know the moment maintenance is required, even if you're away from the device.
- VCSEL and Active Toner Density Control^o Create output with brilliant colors and smooth gradations for sharper text and more precise reproductions.
- Oversize and Heavy Media Support°
 Handle more types of media, including up to 13" × 19" standard paper sizes, a 38" oversize option, and heavy media up to 173 lb. cover (470 gsm), and keep more jobs in-house.

Media Identification Unit^o

Eliminate guesswork during print production prep work and easily associate media with the closest available match in your media library.

- Paper Trays (Standard)°
 With a total paper capacity of 4,400 sheets, you can print with fewer reloads. Increase capacity to 18,100 sheets with optional paper sources.
- Active Tray Indicators

 Find out which tray is currently being fed into the printer so you can refill other paper sources without interrupting the run.
- Vacuum Feed Large Capacity Input Tray
 Type S14*
 Ensure paper feeds run continuously with a

Ensure paper feeds run continuously with a three-belt air-blasting tool that handles coated papers up to 173 lb. cover (470 gsm).

Bridge Unit (BU5020)*

Extend print runs and minimize interruptions by bridging three 4,400 sheet trays.

Vacuum Feed LCIT (RT5150)*

4,400-sheet Vacuum Feed LCIT can handle paper sizes up to 13" \times 19.2" and paper weights up to 173 lb. cover (470 gsm).

- Cover Interposer Tray (CI5040)*

 Feed pre-printed sheets for fast production of front and back covers.
- Plockmatic High Capacity Interposer°
 Use for automatically inserting pre-printed offset prints, front covers, back covers or tabs into your finishing workflow.
- Multi Bypass Tray (BY5020)*

 Feed up to 500 sheets of specialty stocks, including sizes up to 49.6" and expand what you can offer customers.

^{*}Optional

[°]Not shown

Best-in-class media support so you can expand your business

Produce everything from flyers, direct mail and promotional materials to packaging, catalogs, photo books, POP and much more. The RICOH Pro C9500 makes it easy to take on more creative applications and expand your business with support for thin to thick paper, and synthetic and specialty substrates. Superior mixed media handling keeps jobs running continuously, avoiding production slowdowns.

Inline finishing helps you save on outsourcing

Adding inline finishing solutions will help you save on outsourcing, gain more control over the outcome and impress customers. Confidently finish high-class saddle-stitched booklets, ring-bound books, and folded direct mail — efficiently and affordably. Whether you need to collate, bind or trim on simple or complex jobs, we'll help you automate everything so there are fewer steps, fewer manual errors and faster turnaround times.



Enter markets where color accuracy and pristine pages are essential

Produce photo-like images with crisp text and fine lines, sheet after sheet, with 2400×4800 dpi resolution. Groundbreaking and world-first technologies like Auto Color Diagnosis and Image Quality Monitoring take operator subjectivity out of the equation. Internal scanners automatically detect imperfections and instantly adjust to maintain consistency and avoid costly reprints. Gloss Control is another exciting new feature exclusive to the RICOH Pro C9500. It enables operators of all levels to achieve high-end, offset-like quality while accelerating your digital migration strategy.

A simplified user experience

Intuitive and highly intelligent automated features on the RICOH Pro C9500 empower a new generation of operators to succeed, regardless of skill level. Move jobs through the workflow while leveraging the system's most advanced capabilities. An embedded NBC (New Based Controller) — new for this model and specifically designed for complex graphic communication workflows — can support a highly synchronized remote diagnosis system and enable remote service.

Services that deliver new pathways to success

With Ricoh, your experience will be smooth from the start. Gain the support of an exceptional and knowledgeable professional services team who brings real-world experience to every engagement. From operator training to finishing solutions, business development and G7 certification, tap into Ricoh as your single-source partner to help you get the most out of your investment and develop a deeper customer base.

Operate your shop more productively. Service your customers more profitably.



Find out more at www.ricoh-usa.com/rgc

Hardware Specifications

Process 4-drum dry electrostatic transfer system with internal transfer belt Oil-less belt-fusing method Fusing Pro C9500 – 115 ppm (8.5" × 11") Pro C9500 – 135 ppm (8.5" × 11") with Engine Speed Productivity Upgrade Kit

Max Monthly Volume 1,000K

1 750K

Duty Cycle Laser Resolution 2400 × 4800 dpi VCSEL Warm-Up Time Limitless Paper Supply Less than 540 sec. Supported 13" × 19.2" – 13" × 49.6"

Paper Size

13" x 19.2" – 13" x 49.0" (when using Oversize Tray Option) 12.7" x 18.9" – 12.7" x 49.4" (when using Oversize Tray Option) Trays 1 – 4: 40 – 470 gsm Duplex: 40 – 470 gsm Trays 5 – 8: 52 – 400 gsm Maximum Printable Paper Weight

Bypass Tray: 52 – 216 gsm Uncoated Paper, Coated Paper (gloss

Paper Type and matte), Recycled Paper, Pre-printed, Letterhead, Pre-

punched, Tab Stock, Textured Paper, Label Paper, Carbonless Paper

Trays 1 – 8: 2,200 sheets per tray Bypass Tray: 500 sheets Paper Capacity

Total Standard Capacity: 4,400 sheets
Total Optional Capacity: 18,100 sheets
208-240V, less than 60A (30A × 2),

50/60 Hz

Max. Power Less than 9,000W

Consumption Typical Electricity Pro C9500: 39.3kWh/week Consumption (TEC)* Pro C9500: 36.2kWh/week *Typical Electricity Consump tion by ENERGY STAR® program

ENERGY STAR Certified **EPEAT**

Power Source

Silver (N-50 & N-70 Controller)

Dimensions (W \times D \times H) 99.2" × 39" × 59"

Height: 73.6" when including status

Less than 2,373 lb.

Printer Controllers

Fiery Controller N-50

Weight

Fiery System Version Fiery FS500 Pro Configuration External Memory 32GB RAM (4GB x 8) CPU Intel Core® i5-8500 processor

SSD Boot Drive for OS and Fiery software + 1TB HDD HDD Operating System Windows 10 IoT Enterprise 2019 LTSB

Fiery Controller N-70

Fiery System Version Fiery FS500 Pro External 32GB RAM (4GB x 8) Configuration Memory

Dual Intel® Xeon 12-core processor SSD Boot Drive for OS and Fiery CPU software + 2 x 2TB HDD Windows 10 IoT Enterprise Operating System

2019 LTSB

Accessories

Vacuum Feed Large Capacity Tray (LCIT RT5150)

(Max 3 units per system)

Paper Capacity ,400 sheets (2,200 sheets x 2 Trays) $3.94" \times 5.5" - 13" \times 19.2$ Paper Size Trays 3 – 4: 40 – 470 gsm Trays 5 – 8: 40 – 400 gsm Paper Weight 41.5" × 28.7" × 39.4"

Dimensions (W x D x H) 507 lbs. Weight

Vacuum Feed Oversize Tray Type S9

Paper Capacity 730 sheets Paper Size Paper Weight

730 sheets 8.27" × 16.54" – 13" × 27.5" 52 – 400 gsm Width of LCIT RT5120 will extend to 50.8"

Extension Vacuum Feed Banner Sheet Tray Type S14
Paper Capacity 500 sheets
Paper Size 8.27" × 16.54" - 13" × 38" 52.3 - 470.0 gsm (16.54" - 19.2") 52.3 - 300.0 gsm (19.3" - 27.5") 63.1 - 300.0 gsm (27.6" - 38") Paper Weight

Multi Bypass Tray Unit (BY5020)

500 sheets 3.94" × 5.5" - 13" × 19.2" Paper Capacity Paper Size

Maximum paper size extends up to 13" × 27.5" by adding the optional Multi Bypass Sheet Tray Type S9

Paper Weight 52 - 216 gsm

Cover Interposer Tray (CI5040)

400 sheets (200 sheets x 2 Trays) 5.5" x 8.5" – 13" x 19.2" 52 – 350 gsm Paper Capacity Paper Size Paper Weight Air Assist
Double Feed Detection Supported Optional

Dimensions (W \times D \times H) $13" \times 28.7" \times 50.8"$ Weight 110 lbs.

 4,500-Sheet Finisher with 100-Sheet Stapler (SR5110)

 Paper Capacity
 Lower Shift Tray: 3,500 sheets

 Upper Shift Tray: 1,000 sheets
 Lower Shift Tray: 52 - 470 gsm

 Lower Shift Tray: 52 - 470 gsm

 Upper Shift Tray: 52 - 350 gsm Optional 2/3 hole 39.2" × 28.7" × 55.7 Punch

Dimensions (W x D x H) Weight 298 lbs

3,500-Sheet Booklet Finisher with 100-Sheet Stapler (SR5120)

Lower Shift Tray: 2,500 sheets Upper Shift Tray: 1,000 sheets Paper Capacity Lower Shift Tray: 52 – 470 gsm Upper Shift Tray: 52 – 350 gsm Paper Weight

Punch Optional 2/3 hole Saddle Stitch Staple

7.2" × 10.2" – 13" × 19.2"

Paper Size Paper Weight 52 – 350 gsm

52 – 80 gsm up to 30 sheets/120 pages 39.2" × 28.7" × 55.7" Dimensions (W x D x H)

353 lbs. Weight

Booklet Trimmer (TR5050)

One Side Edge Trimming Type
Trimming Capacity Up to 30 sheets/120 pages 7.2" × 10.2" – 13" × 19.2" Paper Size Stack Capacity Limitless Stack Up to 60 sets Supported 43.9" × 23.3" × 21.9" Dimensions (W \times D \times H)

166 lbs.

High Capacity Stacker (SK5040)Paper Capacity 5,000 5,000 sheets; Proof tray: Additional

250 sheets 52 – 470 gsm

Paper Weight Rollaway Cart Standard and Optional additional

carts available 35.4" × 28.7" × 39.8" Stacker: 264 lbs.; Rollaway cart: 33 Dimensions (W \times D \times H)

FD5030 Multi-Folding Unit

Folding Type Single Sheet Mode Z-Fold, Half-Fold/Print inside, Half-Fold/Print outside, Letter Fold-in/

Print inside, Letter Fold-in/Print outside, Letter Fold-out

Half-Fold/Print inside, Half-Fold/Print Multiple Sheets Mode outside, Letter Fold-in/Print inside,

Letter Fold-in/Print outside,

Letter Fold-out

Paper Size Single Sheet

2 folding: 8.5" × 11" – 12" × 18"; Half folding: 8.5" × 11" – 13" × 19.2"; Letter folding: 8.5" × 11" – 12" × 18"; Double

Multiple Sheets Mode

Totaing: 8.5" × 11" – 12" × 18"; Double
Parallel folding: 8.5" × 11" – 12" × 18";
Gate folding: 8.5" × 11" – 12" × 18"
Half Folding: 8.5" × 11" – 13" × 19.2";
Letter Fold-in: 8.5" × 11" – 12" × 18";
Letter Fold-out: 8.5" × 11" – 8.5" × 14"

Paper Weight

Single Sheet Mode Multiple Sheets Mode 64 - 105 gsm 64 – 80 gsm 18.5" × 28.7" × 39.4" Dimensions (W x D x H)

Weight

Plockmatic High Capacity Interposer (HCI3500)

Paper Capacity 3,500 sheets (1,750 sheets \times 2 Trays)

65 – 350 gsm 4.72" × 8.27" – 13" × 26" 47.2" × 28.7" × 43" Paper Weight Paper Size Dimensions (W × D × H) 551 lbs.

Plockmatic MPS - Oversize Sheet Stacker

Paper Capacity Paper Weight

2,000 sheets 150 – 470 gsm 8.5" × 11" (LEF) – 13" × 49.6" 35.4" × 26.8" × 41.8" Paper Size Dimensions (W \times D \times H) (width extends to max 55")

Weight

 Plockmatic Booklet Maker (PBM 350e)

 Paper Size
 8.5" × 11" – 12" × 18"

 Paper Weight
 64 – 300 gsm
 2 - 35 sheets - 80 gsm 55.9" × 35.4" × 27.6" Set Size Dimensions (W x D x H)

Weight Optional 297 lbs.

Trim Module, Book Fold Module, Cover Feeder, Rotate, Crease Trimmer

Plockmatic Booklet Maker PBM 5035/5035S

Staple: 8.11" × 8.27" – 12.6" × 24.4" Stitch: 4.27" × 8.27" – 12.6" × 24.4" Paper Size Paper Weight 18 lb. Bond to 130 lb. Cover (dependent on paper type and quality)

Book Thickness

Min Set: 1 sheet of 20 lb. Bond Max Finished Book: 0.393" (approx 200

pages 20 lb. Bond) Max Set: 0.137" or 0.196" (approx 35

sheets and 50 sheets of 20 lb. Bond)

Weight

GBC StreamPunch Plus Punched Paper Sizes 5.5" \times 8.5" , 8.5" x 11", 8.5" x 14", 11" \times 17", 12" \times 18"

Punched Media 75 - 300 gsm Weight Range Tab Punching Supported "Two-Up" Punching Dimensions (W × D × H) Supported 17.5" × 28.7" × 39.4"

220 lbs.

GBC StreamWire (GBC StreamPunch Plus is required)

8.5" × 11" (LEF) 75 – 300 gsm 8.5" × 11" (LEF) – 32 loops Black, White or Silver Paper Sizes Paper Weight Number of Loops StreamWire Supply

Up to 30, 50, 60, 70 or 80 Sheets

Tab Stock Supported 34" × 38" × 34" Dimensions (W \times D \times H) Weight 500 lbs.

Additional Accessories

Cover Interposer Tray Cl5030, Perfect Binder GB5010, RPIP Interface Option, Plockmatic LCT 3500 Oversize Tray, Auto Color Diagnosis Unit Type A (includes Image Quality Monitor)

Consumables

CMYK Toners Black yield: 59.8K prints/bottle;

CMY yield: 60.5K prints/bottle* Yield: 220K prints/bottle* Waste Toner Bottle

*Based on 8.75% coverage (LT)

TCRU Program Supported

Workflow Solutions Supported

RICOH ProcessDirector®, RICOH TotalFlow" Producer, RICOH TotalFlow Prep, RICOH TotalFlow Production Manager, RICOH TotalFlow BatchBuilder", RICOH @Remote, DigitalStoreFront®, CGS/ORIS Lynx & Evaluate, Color Profiler Suite, EFI Fiery Graphic Arts Package Premium Edition, DirectSmile®, EFI Fiery Central, Objectif Lune

Specifications are subject to change without notice.

Contact Ricoh for a list of certified media.



www.ricoh-usa.com/rgc





Ricoh USA, Inc., 300 Eaglewiew Blvd, Exton, PA 1934.1, 1-800-63-RICOH
2025 Ricoh USA, Inc. All rights reserved. Ricoh⁸ and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners.
The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are sho with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequated of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them. Ricoh USA, Inc., 300 Eagleview Blvd, Exton, PA 19341, 1-800-63-RICOH