Color Laser MFP



RICOH SP C261SFNw



RICOH SP C261SFNw



Get versatile capabilities at a low cost

If you run a startup or small workgroup, you need a highquality multifunction printer (MFP) that saves you time and offers low long-term costs. The affordable and compact RICOH SP C261SFNw Color Laser MFP is designed for personal users or workgroups of up to three people. You'll get jobs moving quickly with print and copy speeds of up to 21 pages per minute (ppm) and easy connectivity from your smartphone or tablet. And with a low TEC value of 1.5 kWh, ENERGY STAR® certification and an EPEAT® Silver rating, you'll enjoy low energy usage.

Deliver high-impact communications fast

At up to 2400 x 600 dpi resolution, you can still print 21 ppm to deliver documents with vivid color and crisp black text quickly. Plus, the single pass document feeder (SPDF) lets you load up to 50 pages for uninterrupted scanning at up to 40 images per minute (ipm).*

Create a user-friendly workstation

Simplify scan, print, copy and fax jobs with the 4.3" color touchscreen—store up to 12 settings for quick access to common tasks. Load up to three different paper sizes and increase paper capacity to 751 sheets with an optional paper tray to increase efficiency. Plus, with the easy-setup installation wizard, you'll hit the ground running in no time.

*Maximum speed for scanning black-and-white documents. The maximum scan speed for color documents is 24 ipm

Part # 408235

21 ppm

Desktop, Color Laser

Up to 1,500 prints/30,000 prints 14 seconds/30 seconds

600 x 600 dpi (Default) (Speed Mode)

1200 x 600 dpi equivalent (Standard Mode), 2400 x 600 dpi equivalent (Fine Mode)

250-sheet tray + 1-sheet Bypass Tray/ 751 sheets

Standard Tray/Bypass Tray: 3.54" x 5.83"-8.5" x 14.0" Standard Tray: 16–43 lb Bond/90 lb, Index (60–160 g/m²) Optional Tray: 16–28 lb. Bond (60–105 g/m²) Duplexing: 16–24 lb. Bond (60–90 g/m²)

Electro-photographic printing Flatbed Scanner with full color Contact Image Sensor (CIS)

Dry mono-component toner developer, AIO Cartridge

System Specifications

Engine Specifications

Ricoh SP C261SFNw Configuration/Technology Printing Process Scanning Element Toner Type Color/B&W Print Speed (Letter) Max. Monthly Volume/Duty Cycle First Page Out/Warm Up Time Print Resolution

Standard/Max Paper Capacity Standard Output Capacity Supported Paper Sizes Supported Paper Weights

Supported Paper Types

Bond*, Cardstock*, Color, Label*, Letterhead, Plain, Pre-printed, Pre-punched, Thick, Thin & Recycled papers, Envelopes* (*via Standard Tray and Bypass only)

29 seconds

Certified Silver

120V. 60Hz. 11A

Automatic (standard)

150 sheets

Duplexing Dimensions (W x D x H) Weight Power Consumption

6.5" x 19.4" x 18.1" (420 x 493 x 460 mm) 63.9 lbs. (29.0 kg) Operating: B&W: 331.3 W, Color: 404.1 W, Sleep Mode: 1.3 W Typical Electricity Consumption (TEC) 1.5 kWh/week Recovery from Sleep Mode **Power Requirements** ENERGY STAR EPEAT



www.ricoh-usa.com

Ricoh USA, Inc., 70 Valley Stream Parkway, Malvern, PA 19355 1-800-63-RICOH @2017 Ricoh USA, Inc. All rights reserved. Ricoh* and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in there materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them. R3889-1 R3889-1

Copy Specifications

Copy Resolution Document Feeder Type Document Feeder Capacity Document Feeder Original Size Document Feeder Paper Weight Maximum Original Size

Maximum Copy Quantity Reduction & Enlargement Ratios Zoom Range

Copier Features

Auto Duplex, Combine Copy (2-in-1, 4-in-1), Electronic Sort, ID Card Copy, Image Density, Image Quality Mode (Text, Photo, Mixed), Memory Copy, Auto Tray Switch, Series Copy

Print Specifications

Processor Speed Memory (Standard/Maximum) Printer Languages Connection Type Font Support Network Protocols Supported Operating Systems

Device Management Utilities Mobile Printing

Other Print Features

1–999 Set Quantity, Collate, Dithering, Duplexing, Do Not Print Blank Pages, Front Cover, Layout/N-up Printing, Locked Print, Mirror Image Print, Reduce/Enlarge Print, Rotate Print, User Codes, User ID, Watermarks, Economy Color

Scan Specifications

Scanner Resolution Scanning Speed (Letter) Platen Size Maximum Scanning Size Scan Modes **File Formats** Scan-To Modes

Scan Protocols

Facsimile Specifications

Fax Resolution Fax Scanning Speed Modem Speed Fax Compression Method Fax Memory Transmission Speed

Quick Dials/ Speed Dials Standard Fax Features

Security Features

H

P

Pi

Wireless LAN Security-WEP, WPA2, Network Security via TCP/IP Access Control, Encrypted Communication using IPsec, IPP Authentication, Locked Print, User Restrictions

| Hardware Options | |
|-------------------------|---|
| Paper Feed Unit TK1220 | Part # 407890 |
| Paper Capacity: | 500 sheets |
| Supported Paper Sizes: | Fixed for 8.5" x 11" / Letter, A4 |
| Supported Paper Weight: | 16-28 lb Bond (60–105 g/m ²) |
| Dimensions (W x D x H): | 15.7" x 17.7" x 5.0" (400 x 450 x 127 mm) |
| Weight | 8.8 lbs. (4 kg) |
| | |

Consumables and Yields

| rint Cartridge Black SP C250A | 2,300 pages* | Part # 407539 |
|---------------------------------|--------------|---------------|
| rint Cartridge Cyan SP C250A | 2,300 pages* | Part # 407540 |
| rint Cartridge Magenta SP C250A | 2,300 pages* | Part # 407541 |
| rint Cartridge Yellow SP C250A | 2,300 pages* | Part # 407542 |
| Vaster Toner Bottle SP C220 | 25,000 pages | Part # 406043 |

*Declared yield values in accordance with ISO/IEC 19798. Actual yields may vary based on images printed and other factors.

The RICOH SP C261SFNw ships with starter toner that veilds 1.000 pages (ISO/IEC 19798)

Warranty

The Ricoh SP C261SFNw is under warranty against defects for a period of one year from the date of purchase. Consumables are under warranty for period of 90 days from the date of purchase or until depleted, whichever comes first.

Please refer to warranty documents shipped with the product for more details.

Single Pass Document Feeder (SPDF) 50 Sheets 55" x 5.5" to 8.5" x 14" (140 x 140 mm to 216 x 356 mm) 14-28 lb. Bond (52-105 g/m²) Platen: Up to 8.5" x 11.7"/A4 (210 x 297 mm), SPDF: Up to 8.5" x 14" (216 x 356 mm) 99 copies 50%, 65%, 78%, 93%, 129%, 155%, 200%, 400% 25% to 400% in 1% increments

600 x 600 dpi (Platen), 300 x 600 dpi (SPDE)

400 MHz 256MB RAM PCL6/5c, PostScript 3, PictBridge 10Base-T/100Base-TX, USB 2.0 Type B, USB 2.0 Type A, IEEE802.11b/g/n PCL/PS3: 80 fonts TCP/IP, IPP, Bonjour Windows Vista, 7, 8.1, 10, Systems Server 2008/R2, Server 2012/R2, Macintosh: OS X 10.9–10.12, Linux and Unix Filter Ricch @Remote, Ricch Device Manager NX, Ricch Print Driver Packager NX RICOH Smart Device Connector App (for printing only) Ricch SP C260 Series Scan App (for scanning only), Apple AirPrint®, Google Cloud Print®, Mopria®

Color and B&W: up to 600 dpi, TWAIN: up to 1200 dpi B&W: up to 40 ipm, Color: up to 24 ipm Up to 8.5" x 11"/A4 Up to 8.5" x 14"

Black & White, Grayscale, Color JPEG, Single/Multi Page TIFF, Single/Multi Page PDF Scan-to-Email; Scan-to-Folder (SMB/FTP); Scan-to-Media (USB); TWAIN/WIA, ICA, SANE Scanning Network: TCP/IP; Email: SMTP; Scan-to-Folder: SMB, FTP

Up to 200 dpi Less than 5 seconds/page (Letter @ 200 dpi) 33.6 kbps with auto fallback MH, MR, MMR, JBIG 100 pages (2.5 MB Flash ROM) Approximately 3 seconds/page* *ITU No.1 chart, Compression: MMR, Resolution: Standard speed: 33.6 Kbps 20/200 LAN-Fax (Outbound TX only), Internet Fax (T.37), Fax Forwarding to E-Mail/Folder, PSTN, PBX