

A4 Multifunction Colour

# IM C401F IM C401SRF

✔ Printer   ✔ Copier   ✔ Scanner   ✔ Fax

**RICOH**  
imagine. change.



IM C401F  
IM C401SRF



45-ppm

# Powerful Features. Vibrant Results. Effortless Office Productivity.

Transform the way you work with the RICOH IM C401F and IM C401SRF. These A4 colour multifunction printers (MFPs) deliver robust functionality, wide software compatibility, and an intuitive design that empower fast-paced offices. Whether printing, copying, scanning, or faxing, these models enable your team to share information quickly, securely, and with vibrant colour.

Delivering professional-quality output, these devices are ideal for organizations seeking a balance between functionality, sustainability, and cost-efficiency, all in a space-saving design.

## Key features:



### Seamless Performance

Streamline your workflow with integrated print, copy, scan, and fax capabilities, enhanced by Ricoh's embedded software solutions for remote management, mobile connectivity, and document processing.



### Superior Print Performance

Achieve fast print speeds of up to 45 ppm and crisp 1,200 x 1,200 dpi resolution, delivering vibrant colours and sharp, precise text for professional-grade documents.



### Sustainable Design

Drive your sustainability efforts with ENERGY STAR® certified MFPs, featuring 10% post-consumer recycled content, 42% less plastic packaging compared to previous models, and a sleep mode that cuts the power consumption of the Smart Operation Panel (SOP) by 45% when compared to previous generation models.



### Advanced Security Features

Keep confidential information secured from unauthorized access with user authentication and the Erase All Memory function, which overwrites the drive at the end of life. Enable secured printing with advanced encryption and enhanced network security through features such as IEEE 802.11, 802.1x, and validate firmware and applications with Trusted Platform Module (TPM) 2.0.



### User-Friendly Design

Boost productivity with the intuitive 10.1" SOP which simplifies navigation, while integrated stapling on the IM C401SRF makes finishing tasks effortless.



## Simplifying Office Work, Empowering Productivity

The RICOH IM C401F and IM C401SRF are built to address the unique challenges of modern offices, providing reliable and efficient solutions for teams who need to quickly share and process information.

Whether it's scanning to digitize documents, printing high-quality colour outputs, or securely managing sensitive data, these A4 colour MFPs offer an efficient, streamlined solution.

With a focus on sustainability, data security, and intuitive operation, Ricoh ensures these devices support your goals while enhancing productivity and reducing operational complexity.

# RICOH IM C401F/ IM C401SRF

## MAIN SPECIFICATIONS

| GENERAL  | IM C401F   | IM C401SRF                |
|--|--|---------------------------|
| Warm-up time   | Less than 24 seconds   |                           |
| Recovery time  | 10 seconds   |                           |
| First copy time (B/W / Full Colour)                      | 6.2 seconds / 7.4 seconds  | 6.7 seconds / 7.9 seconds |
| First print time (B/W / Full Colour)                     | 4.2 seconds / 5.4 seconds  | 4.8 seconds / 5.9 seconds |
| Continuous output speed                                  | B/W: 45 ppm / 45 ppm (simplex / duplex)<br>Full Colour: 42 ppm / 38 ppm (simplex / duplex)   |                           |
| Memory: standard   | 6GB (2GB mainframe and 4GB SOP)  |                           |
| Storage  | 256GB SSD (Standard); 320GB HDD (Optional);<br>256GB FIPS-validated Enhanced Security SSD (Optional)   |                           |
| Single-Pass Document Feeder (SPDF) capacity              | 50 sheets  |                           |
| Weight   | 50 kg / 110.2 lbs  | 60 kg / 132.3 lbs         |
| Dimensions: W x D x H                                    | 19.6" x 22.2" x 23.2"  | 24.2" x 22.2" x 27.8"     |
| Power source   | 120V-127V, 60Hz  |                           |
| COPIER   |  |                           |
| Multiple copying   | Up to 999 copies   |                           |
| Resolution   | Up to 600 x 600 dpi  |                           |
| Zoom   | From 25%-400% in 1% increments   |                           |
| PRINTER  |  |                           |
| CPU  | Intel ApolloLake-I E3930 1.3GHz  |                           |
| Printer language: standard                               | PCL5e/XL, PostScript®3™ Emulation, PDF Direct Print Emulation, MediaPrint: JPEG, TIFF  |                           |
| Printer language: optional                               | Genuine Adobe® PostScript®3™, Adobe® PDF Direct Print  |                           |
| Print resolution: maximum                                | Up to 1200 x 1200 dpi  |                           |
| Network interface: standard                              | Mainframe: IEEE 802.11 a/b/g/n/ac - 2.4 GHz or 5 GHz can be selected;<br>Ethernet 10BASE-T/100BASE-TX/1000BASE-T;<br>USB Host Type A - USB Flash Memory, USB Host Type A - 1 port for optional keyboard or card reader                               |                           |
| Network interface: optional                              | Device Server Option (additional NIC port)   |                           |
| Mobile printing capability                               | AirPrint, Mopria®, RICOH Smart Device Connector  |                           |
| Fonts: standard  | 80 Roman fonts + 13 International fonts  |                           |
| Fonts: PS3 optional                                      | 136 Roman fonts  |                           |
| Windows® environments                                    | Windows 10 (32-/64-bit), 11, Server 2016, Server 2019, Server 2022, Server 2025  |                           |
| Mac OS environments                                      | MacOS 10.11 and later (PostScript®3™ only)   |                           |
| SAP® environments  | SAP R/3, SAP S/4   |                           |
| SCANNER  |  |                           |
| Scanning speed: BW / Full Colour                         | 41 ipm (simplex) / 82 ipm (duplex)   |                           |
| Resolution: maximum                                      | Up to 600 dpi  |                           |
| Compression method                                       | B/W: TIFF (MH, MR, MMR, JBIG2), Colour: JPEG   |                           |
| File Formats   | Single Page: TIFF, JPEG (greyscale or full colour), PDF, High Compression PDF, PDF/A, Encrypted PDF, Searchable PDF (OCR Option required)<br>Multi Page: TIFF, PDF, High Compression PDF, PDF/A, Encrypted PDF, Searchable PDF (OCR Option required) |                           |
| Scan modes   | Network: TCP/IP, Sending E-mail: SMTP, POP, IMAP4, Scan to Folder: SMB, FTP, Web Services on Devices for Scanning, Network TWAIN for Windows environments  |                           |
| FAX  |  |                           |
| Circuit  | PSTN, PBX  |                           |
| Transmission speed                                       | 3 seconds  |                           |
| Modem speed: maximum                                     | 33.6 Kbps  |                           |
| Resolution: standard                                     | 8 x 3.85 line/mm, 200 x 100 dpi (std.), 8 x 7.7 line/mm, 200 x 200 dpi (Detail, Photo)   |                           |
| Compression method                                       | MH, MR, MMR, JBIG  |                           |
| Scanning speed (Simplex / Duplex; BW and Colour, LT SEF) | 40 / 80 ipm  |                           |
| Memory   | 8 MB (320 pages)   |                           |

# RICOH IM C401F/ IM C401SRF

## MAIN SPECIFICATIONS

| PAPER HANDLING   |  | IM C401F       | IM C401SRF |
|--|--|----------------|------------|
| Supported paper size   | Standard Paper Tray: Up to 8.5" x 11" / A4, Optional Paper Tray: Up to 8.5" x 14", Envelopes, Bypass: Up to 8.5" x 14", Postcard, Envelopes  |                |            |
| Paper input: standard  | 550-Sheet Tray, plus 100-Sheet Bypass  |                |            |
| Paper input: maximum   | 2,300 Sheets<br>(standard 550-sheet tray, plus 100-sheet bypass tray and 3 optional 550-sheet paper feed units)  |                |            |
| Paper output: standard   | 100 sheets (face down), 250 sheets (internal finisher)   |                |            |
| Paper weights  | Standard Trays: 60 - 163 g/m <sup>2</sup> , Bypass Tray: 60 - 220 g/m <sup>2</sup> , Duplex Unit: 60 - 163 g/m <sup>2</sup>  |                |            |
| Paper types  | Plain Paper, Recycled Paper, Colour Paper, Letterhead, Preprinted Paper, Bond Paper, Cardstock, Label Paper, Waterproof Paper, Envelope, Coated Paper, Thick Paper 1–3   |                |            |
| SECURITY FEATURES  |  |                |            |
| Prevent unauthorized access to device  | 802.1x Wired Authentication, IEEE 802.11 Security (WEP, WPA, WPA2, WPA3), Quota Setting/Account Limit, User Authentication – Windows, LDAP via Kerberos, Basic, User Code Authentication, Wi-Fi Protected Setup (WPS) Support                                    |                |            |
| Prevent unauthorized access to network   | IP Filtering – Access Control, IPsec Communication, Network Protocol On/Off, S/MIME, SMTP Over SSL/TLS, Secure Sockets Layer (SSL) Communication, Transport Layer Security (TLS 1.3), Network User Authentication  |                |            |
| Protection of confidential information   | HDD/SSD Encryption, Trusted Platform Module (TPM) 2.0, Authentication Password Encryption, Unauthorized Copy Prevention – Print and Copy, Compulsory Security Stamp, Mask Type for Copying/Data Security for Copying, Encrypted Secure Print, Encrypted PDF Mode |                |            |
| Protection of latent data  | Erase All Memory function – to overwrite drive and NVRAM at machine end-of life<br>Auto Erase Memory available when optional HDD is installed  |                |            |
| ENVIRONMENTAL FEATURES   |  |                |            |
| Power consumption: maximum   | 1,400 W or less  |                |            |
| Power consumption: ready / sleep   | 80 W or less / 0.50 W  |                |            |
| Typical Energy Consumption (TEC)   | 0.50 kWh   | 0.52 kWh       |            |
| ENERGY STAR®   | Certified  |                |            |
| EPEAT®   | Gold Rated*  |                |            |
| * EPEAT Gold rating is applicable only in the USA.   |  |                |            |
| CONSUMABLES  |  |                |            |
| Toner (standard-yield black)*  | Black Toner Cartridge: 19,300 prints   |                |            |
| Toner (standard-yield cyan/magenta/yellow)*  | Colour Toner Cartridges: 10,300 prints each  |                |            |
| Toner (high-yield black)*  | Black Toner Cartridge: 19,800 prints   |                |            |
| Toner (high-yield cyan/magenta/yellow)*  | Colour Toner Cartridges: 13,700 prints each  |                |            |
| Staple set   | N/A  | 5,000 staples  |            |
| Staple refill  | N/A  | 10,000 staples |            |
| * Declared toner yield in accordance with ISO/IEC 19798  |  |                |            |
| PAPER SUPPLY OPTIONS   |  |                |            |
| 550-Sheet Paper Feed Unit PB1230, Low Cabinet Type A12, Medium Cabinet Type A13, High Cabinet Type A14, Caster Table Type A11  |  |                |            |
| OTHER OPTIONS  |  |                |            |
| 1 Bin Tray BN1050, PostScript®3™ Unit Type M59, OCR Unit Type M52, Device Server Option Type M52, HDD Option Type M52 320GB, FIPS-validated Enhanced Security SSD Option Type M52 256GB, Card Reader Cover Type M52, Optional Counter Interface Unit Type M12  |  |                |            |
| Terms and Conditions   |  |                |            |
| <div><div>-</div><div>This device does not support PoE (Power over Ethernet) and should not be connected to a PoE hub. Connecting to a PoE hub could cause damage and void warranty coverage.</div><div>-</div><div>Some options may not be available at the time of market release.</div><div>-</div><div>Specifications are subject to change without notice.</div><div>-</div><div>For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.</div><div>-</div><div>Some features may require additional options and/or charges.</div></div>   |  |                |            |
| <div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div> |  |                |            |



Ricoh Canada Inc., 400-5560 Explorer Drive, Mississauga ON L4W 5M3, 1 888 742-6417  
 ©2025. Ricoh Canada Inc. All rights reserved. Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.