

RICOH
IM C3510SD
IM C4510SD
IM C6010SD

RICOH
imagine. change.



Work smarter. Optimize document workflows. Empower your teams and increase productivity. Meet your business needs — now and in the future.

Intelligent multifunction devices built to evolve with your business and anticipate your changing document workflow needs. Fast-paced organizations need modern technology that provides scalability, relevancy and optimization for high-volume workflows. Our latest series of colour multifunction devices are engineered to meet these demands — offering all the great features you expect in a colour MFP with impressive new scanning features to take your business to a whole new level of productivity and efficiency.



Print, copy, scan and fax (optional)



Production-level scanning capabilities



Output speeds up to 60 ppm



Eco-friendly, compact design



Intuitive Smart Operation Panel



Mobile connectivity options



Automatic firmware updates



Built-in security features



Outstanding support and uptime



Seamless cloud connectivity options



Optional finishing solutions

RICOH IM C3510SD/IM C4510SD/IM C6010SD

MAIN SPECIFICATIONS

GENERAL

Warm-up time	IM C3510SD: 25 seconds IM C4510SD: 24 seconds IM C6010SD: 24 seconds
First print output speed	IM C3510SD: B/W: 4.0 seconds, Full Colour: 6.6 seconds IM C4510SD: B/W: 3.3 seconds, Full Colour: 5.2 seconds IM C6010SD: B/W: 2.4 seconds, Full Colour: 3.8 seconds
Continuous output speed	IM C3510SD: 35 ppm IM C4510SD: 45 ppm IM C6010SD: 60 ppm
Memory: standard/maximum	Mainframe 4GB + SOP 4GB
Storage: standard	256GB Solid State Drive (SSD)
Single-Pass Document Feeder (SPDF) capacity	300 sheets
Weight	IM C3510SD: 225 lbs. (102 kg) IM C4510SD: 227 lbs. (103 kg) IM C6010SD: 227 lbs. (103 kg)
Dimensions: W x D x H	23.1" x 27.6" x 40.6" (587 mm x 701 mm x 1,031 mm)
Power source	120V-127V, 60Hz

SCANNER (STANDARD)

Scanning speed: SPDF	100 ipm (simplex) / 200 ipm (duplex)
Resolution: maximum	Up to 600 dpi optical
Drivers	TWAIN / Network TWAIN
File Formats	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encrypted PDF, Searchable PDF* Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encrypted PDF, Searchable PDF*
Scan destination types	E-mail, Folder, USB, URL, FTP
Automatic image adjustment	Image deskew, image rotation, image size
Document Types	Plain paper (38-413 gsm), carbonless paper, plastic cards (up to 1.4 mm thick)

* Requires optional OCR Unit Type M52 or optional software.

PRINTER (STANDARD)

CPU	Intel Apollo Lake 1.6GHz
Printer language: standard	PCL5 (emulation), PCL6, PostScript® 3™ (emulation), PDF direct (emulation)
Printer language: optional	Genuine Adobe® PostScript®3™, PDF Direct from Adobe®
Print resolution	Up to 1200 x 1200 dpi
Network interface: standard	Ethernet 10 BASE-T/100 BASE-TX/1000 BASE-T, USB Host I/F Type A, USB Device I/F Type B
Network interface: optional	Wireless LAN (IEEE 802.11a/b/g/n/ac)
Mobile printing capability	Apple AirPrint™, Mopria®, RICOH Smart Device Connector
Windows® environments	Windows 10/11; Windows Server 2016/2019/2022/2025
Mac OS environments	MacOS v10.15 or later

COPIER (STANDARD)

Multiple copying	Up to 999 copies
Resolution	Up to 1,200 dpi
Zoom	From 25%-400% in 1% increments

RICOH IM C3510SD/IM C4510SD/IM C6010SD

MAIN SPECIFICATIONS

FAX (OPTIONAL)

Circuit	PSTN, PBX
Transmission speed	3 seconds (200 × 100 dpi, JBIG, ITU-T (CCITT) Test Chart #1, Memory Transmission)
Modem speed: maximum	33.6 Kbps
Resolution: standard	8 × 3.85 line per mm, 200 × 100 dpi
Maximum resolution: optional	16 × 15.4 line per mm, 400 × 400 dpi
Compression method	MH, MR, MMR, JBIG
Scanning speed	Up to 94 ppm A4/LT, SEF, standard resolution
Memory: standard	4 MB (320 pages)
Memory: maximum	60 MB (4,800 pages)

PAPER HANDLING

Recommended paper sizes	Tray 1: 8.5" × 11" (A4) Tray 2: 5.5" × 8.5" – 12" × 18" (A3 – A6, B4 – B6), Envelopes Bypass: Up to 12" x 18", Custom sizes: Width: 3.5" – 12.6" (90 – 320 mm), Length: 5.8" – 49.6" (148 – 1260mm)
Paper input: standard	1,200 sheets (2 x 550 sheets+ 100-Sheet Bypass Tray)
Paper input: maximum	4,850 sheets
Paper output: standard	500 sheets 8.5" × 11" (A4) or smaller; 250 sheets 9.8" × 13.9" (B4) or larger
Paper output: maximum	IM C3510SD: 1,625 sheets IM C4510SD: 3,625 sheets IM C6010SD: 3,625 sheets
Paper weight	Standard Trays: 60 – 300 g/m ² Bypass Tray: 52 – 300 g/m ² Duplex Unit: 52 – 256 g/m ²
2 × 550-sheet Paper Tray: optional	Paper size: 5.5" × 8.5" to 12" × 18" (A6 – A3), Paper weight: 60 – 300 g/m ²
1,650-sheet Side Large Capacity Tray: optional	Paper size: 8.5" × 11" (A4, B5), Paper weight: 60 – 300 g/m ²
2,000-sheet Large Capacity Tray: optional	Paper size: 8.5" × 11" (A4), Paper weight: 60 – 300 g/m ²
Paper types	Plain, Recycled, Special, Coloured, Letterhead, Cardstock, Pre-printed, Coated, Envelope, Label, Gloss

ENVIRONMENTAL FEATURES

Power consumption: maximum	Less than 1,584 W
Power consumption operation	IM C3510SD: B/W: 521 W, Full Colour: 588 W IM C4510SD: B/W: 601 W, Full Colour: 683 W IM C6010SD: B/W: 760 W, Full Colour: 869 W
Power consumption: ready/sleep	IM C3510SD: 62.2 W / 0.3 W IM C4510SD: 62.7 W / 0.32 W IM C6010SD: 62.7 W / 0.32 W
Typical Energy Consumption (TEC)	IM C3510SD: 0.36 kWh / week IM C4510SD: 0.45 kWh / week IM C6010SD: 0.67 kWh / week
ENERGY STAR®	Certified
Ecologo®	Certified*
EPEAT®	Gold Rated**

* Ecologo certificate is applicable only in Canada.

** EPEAT Gold rating is applicable only in the USA.

RICOH IM C3510SD/IM C4510SD/IM C6010SD

MAIN SPECIFICATIONS

OUTPUT TRAYS AND FINISHING OPTIONS

Internal Multi-fold Unit	Z folding: A3, B4, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio), 12" × 18" Inner/Outer three-folding: A3, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio) Paper weights for folding: Single Sheet mode: 64 – 105 g/m ² , Multiple Sheet mode (three-fold only): 64 – 80 g/m ²
Internal Shift Tray	Tray capacity: 250 sheets with 80 g/m ² paper (A4, LT or smaller), 125 sheets with 80 g/m ² paper (B4, LG or larger); Paper size: 12.60" × 23.62" or smaller; 52 – 300 g/m ² This option is not available on the IM C3510SD.
One-bin Tray	Tray capacity: 125 sheets, Paper size: 5.5" × 8.5" to 12" × 18" (A5 – A3); Paper weight: 52 – 300 g/m ²
500-sheet Internal Finisher	Paper size: 5.5" × 8.5" to 12" × 18" (A6 – A3); Paper weight: 52 – 300 g/m ² ; Staple capacity: 50 sheets (8.5" × 11") (A4), 30 sheets (8.5" × 14" or larger, and/or Mixed Sizes) (B4 – A3); Staple paper size: 7.25" × 10.5" to 11" × 17" (B5 – A3); Staple paper weight: 52 – 105 g/m ² ; Staple positions: Top, Bottom, 2 staples
1,000-sheet Hybrid Finisher	Paper size: Proof Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Shift Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3), Paper weight: 52 – 300 g/m ² , Staple capacity: 50 sheets; Staple paper size: 8.5" × 11" to 12" × 18" (A4 – A3); Staple paper weight: 52 – 105 g/m ² ; Staple positions: Top, Bottom, 2 staples
1,000-sheet Booklet Finisher	Paper size: Proof Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Shift Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Booklet Tray: 8.5" × 11" to 12" × 18" (A4 – A3); Paper weight: 52 – 300 g/m ² ; Staple capacity: 50 sheets (8.5" × 11") (A4), 30 sheets (8.5" × 14" or larger, and/or Mixed Sizes) (B4 – A3); Staple paper size: Normal Staple: 8.5" × 11" to 12" × 18" (A4 – A3); Saddle Stitch: 8.5" × 11" to 12" × 18" (A4 – A3); Staple paper weight: 52 – 105 g/m ² ; Staple positions: Top, Bottom, 2 staples, Booklet
3,000-sheet Finisher (IM C4510SD/IM C6010SD only)	Paper size: Proof Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Shift Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Paper weight: 52 – 300 g/m ² ; Staple capacity: 65 sheets; Staple paper size: 8.5" × 11" to 12" × 18" (A4 – A3); Staple paper weight: 52 – 105 g/m ² ; Staple positions: Top, Bottom, 2 staples, Booklet
3,000-sheet Booklet Finisher (IM C4510SD/IM C6010SD only)	Paper size: Proof Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Shift Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Booklet Tray: 8.5" × 11" to 12" × 18" (A4 – A3); Paper weight: 52 – 300 g/m ² ; Staple capacity: 65 sheets, Staple paper size: Normal Staple: 8.5" × 11" to 12" × 18" (A4 – A3); Saddle Stitch: 8.5" × 11" to 12" × 18" (A4 – A3); Staple paper weight: 52 – 105 g/m ² ; Staple positions: Top, Bottom, 2 staples, Booklet

CONSUMABLES

Toner	IM C3510SD: Black: 31,000 prints, Cyan/Magenta/Yellow: 19,000 prints IM C4510SD: Black: 42,000 prints, Cyan/Magenta/Yellow: 28,000 prints IM C6010SD: Black: 42,000 prints, Cyan/Magenta/Yellow: 28,000 prints
-------	--

Consumable yields based on 5% coverage on A4 paper.

OTHER OPTIONS

OCR Unit, Adobe® PostScript® 3™ Unit, Unicode Font Package for SAP® 1 License, Fax Option, Fax Memory Unit, G3 Interface Unit (adds a second fax line, 2 max.), Bridge Unit, 1 Bin Tray, Punch units, Stapleless Unit, Cabinet, Card Reader Cover, Enhanced Security SSD, HDD 320GB, IEEE 802.11a/b/g/n/ac Interface, Counter Interface, Power Filter, Fiery Color Controller E26C, Fiery Impose, Fiery Compose, Fiery ColorRight Package, Fiery Automation Package, Fiery Color Profiler Suite, ES-3000 spectrophotometer, Fiery ColorGuard, IQ Manage, Fiery JobFlow

Terms and Conditions

- This device does not support PoE (Power over Ethernet) and should not be connected to a PoE hub. Connecting to a PoE hub could cause damage and void warranty coverage.
- Some options may not be available at the time of market release.
- Specifications are subject to change without notice.
- For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.
- Some features may require additional options and/or charges.



RICOH
imagine. change.

Ricoh Canada Inc., 400-5560 Explorer Drive, Mississauga ON L4W 5M3, 1 888 742-6417

©2025. Ricoh Canada Inc. All rights reserved. Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.