

RICOH IM C3010/ IM C3510



Give your teams the tools, technologies and color capabilities they need to be more creative, collaborative and productive.

Intelligent multifunction devices built for your modern office and workstyle.

Business is taking place beyond the physical office. To be successful, companies need versatile technology that reflects new ways of working and collaborating. Our latest series of color multifunction devices reflect that change — offering an array of impressive features to help your entire organization be more efficient and productive.

- Print, copy, scan and fax (optional)
- Output speeds up to 35 ppm
- Eco-friendly, compact design
- Tablet-like Smart Operation Panel
- Mobile connectivity options
- Automatic firmware updates
- Built-in security features
- Outstanding support and uptime
- Seamless cloud connectivity options
- Optional finishing solutions

RICOH IM C3010/IM C3510 main specifications

General	
Warm-up time	25 seconds
First output speed	IM C3010: B&W: 4.0 seconds, Color: 6.6 seconds IM C3510: B&W: 4.0 seconds, Color: 6.6 seconds
Continuous output speed	IM C3010: 30 ppm IM C3510: 35 ppm
Memory: standard/maximum	4 GB (mainframe) 4 GB (Smart Operation Panel)
Solid State Drive (SSD): standard/maximum	256 GB
Single-Pass Document Feeder (SPDF) capacity	220 sheets
Weight	218.9 lbs./99.3 kg
Dimensions: W × D × H	23.1" × 27.6" × 37.9" (587 × 701 × 963 mm)
Power source	120V – 127V 60Hz
Copier (standard)	
Multiple copying	Up to 999 copies
Resolution	600 dpi
Zoom	From 25% to 400% in 1% steps
Printer (standard)	
CPU	Intel Apollo Lake 1.3GHz
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)
Printer language: option	Genuine Adobe® PostScript® 3™, PDF Direct from Adobe®, IPDS
Print resolution	Up to 1200 × 1200 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B
Network interface: option	Wireless LAN (IEEE 802.11a/b/g/n/ac)
Mobile printing capability	Apple AirPrint®, Mopria®, RICOH Smart Device Connector
Windows® environments	Windows® 8.1, Windows® 10, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019, Windows® Server 2022
Mac OS environments	Macintosh OS X v10.15 or later
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX
SAP® environments	SAP® R/3®, S/4®
Other supported environments	IBM iSeries AS/400 using OS/400 Host Print Transform
Scanner (standard)	
Speed	150 ipm (simplex) 300 ipm (duplex)
Resolution: maximum	Up to 1200 dpi (A5 or smaller paper size)
Compression method	B&W: JBIG2/MH/MMR/MR Color: JPEG
File formats	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, Encrypted PDF, Searchable PDF* Multi Page: TIFF, PDF (Default), High Compression PDF, Encrypted PDF, Searchable PDF* <i>*Requires optional OCR Unit Type M52.</i>
Scan modes	E-mail, Folder, USB, URL, FTP

Facsimile (optional)	
Circuit	PSTN, PBX
Transmission speed	3 seconds (200 × 100 dpi, JBIG, ITU-T (CCITT) test chart #1, memory transmission)
Modem speed: maximum	33.6 Kbps
Resolution: standard	8 × 3.85 line/mm, 200 × 100 dpi
Maximum resolution: option	16 × 15.4 line/mm, 400 × 400 dpi
Compression method	MH, MR, MMR, JBIG
Scanning speed	Up to 94 ppm A4/LT, SEF, standard resolution
Memory: standard	4 MB (320 pages)
Memory: maximum	60 MB (4,800 pages)
Paper handling	
Recommended paper sizes	Tray 1: 8.5" × 11" (A4) Tray 2: 5.5" × 8.5" – 12" × 18" (A3 – A6, B4 – B6), Envelopes Bypass Tray: Up to 12" × 18", Envelopes, Custom Sizes [Width: 3.5" – 12.6" (90 – 320 mm), Length: 5.8" – 49.6" (148 – 1,260 mm)]
Paper input: standard	1,200 sheets
Paper input: maximum	4,700 sheets
Paper output: standard	500 sheets 8.5" × 11" (A4) or smaller; 250 sheets (B4) or larger
Paper output: maximum	1,625 sheets
Paper weight	Trays: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²) Bypass Tray: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²) Duplex: 14 – 68 lb./142 lb. Index (52 – 256 g/m ²)
2 × 550-sheet Paper Tray (PB3320) option	Paper size: 5.5" × 8.5" to 12" × 18" (A6 – A3), Paper weight: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²)
1,500-sheet Side Large Capacity Tray (LCIT RT3050) option	Paper size: 8.5" × 11" (A4, B5), Paper weight: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²)
2,000-sheet Large Capacity Tray (LCIT PB3330) option	Paper size: 8.5" × 11" (A4), Paper weight: 16 – 80 lb./166 lb. Index (60 – 300 g/m ²)
Paper types	Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Coated, Envelope, Label, Gloss
Environmental features	
Power consumption: maximum	Less than 1,584 W
Power consumption: operation	IM C3010: B&W: 473 W, Color: 522 W IM C3510: B&W: 488 W, Color: 548 W
Power consumption	Ready: 46.2 W Sleep: 0.3 W
TEC ¹	IM C3010: 0.30 kWh IM C3510: 0.35 kWh
ENERGY STAR®	Certified
EPEAT®	Gold Rated* <i>*EPEAT Gold rating is applicable only in the USA.</i>

Output trays and finishing options

Internal Multi-fold Unit (FD3020)	Z folding: A3, B4, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio), 12" × 18" Inner/Outer three-folding: A3, A4, DLT, LG, LT, 8.5" × 13.4" (Oficio) Paper weights for folding: Single Sheet mode: 17 – 28 lb./58 lb. Index (64 – 105 g/m ²), Multiple Sheet mode (three-fold only): 17 – 21 lb./44 lb. Index (64 – 80 g/m ²)
Internal Shift Tray (SH3090)	Tray capacity: 250 sheets with 80 g/m ² paper (A4, LT or smaller), 125 sheets with 80 g/m ² paper (B4, LG or larger); Paper size: 12.60" × 23.62" or smaller; Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²)
One-bin Tray (BN3140)	Tray capacity: 125 sheets, Paper size: 5.5" × 8.5" to 12" × 18" (A5 – A3); Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²)
500-sheet Internal Finisher (SR3310)	Paper size: 5.5" × 8.5" to 12" × 18" (A6 – A3); Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²); Staple capacity: 50 sheets (8.5" × 11") (A4), 30 sheets (8.5" × 14" or larger, and/or Mixed Sizes) (B4 – A3); Staple paper size: 7.25" × 10.5" to 11" × 17" (B5 – A3); Staple paper weight: 14 – 28 lb. (52 – 105 g/m ²); Staple positions: Top, Bottom, 2 staples
1,000-sheet Hybrid Finisher (SR3320)	Paper size: Proof Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Shift Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3), Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²), Staple capacity: 50 sheets; Staple paper size: 8.5" × 11" to 12" × 18" (A4 – A3); Staple paper weight: 14 – 28 lb. (52 – 105 g/m ²); Staple positions: Top, Bottom, 2 staples
1,000-sheet Booklet Finisher (SR3330)	Paper size: Proof Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Shift Tray: 5.5" × 8.5" to 12" × 18" (A6 – A3); Booklet Tray: 8.5" × 11" to 12" × 18" (A4 – A3); Paper weight: 14 – 80 lb./166 lb. Index (52 – 300 g/m ²); Staple capacity: 50 sheets (8.5" × 11") (A4), 30 sheets (8.5" × 14" or larger, and/or Mixed Sizes) (B4 – A3); Staple paper size: Normal Staple: 8.5" × 11" to 12" × 18" (A4 – A3); Saddle Stitch: 8.5" × 11" to 12" × 18" (A4 – A3); Staple paper weight: 14 – 28 lb. (52 – 105 g/m ²); Staple positions: Top, Bottom, 2 staples, Booklet

Other options

Adobe® PostScript® 3™ Unit Type M52, Bridge Unit BU3100, Cabinet Type A5, Card Reader Cover Type M52, Enhanced Security SSD Option Type M52 256GB, Fax Memory Unit Type M52, Fax Option Type M52, G3 Interface Unit Type M52, HDD Option Type M52 320GB, IEEE 802.11a/b/g/n/ac Interface Unit Type M52, IPDS Unit Type M52, OCR Unit Type M52, Optional Counter Interface Unit Type M12, Power Filter, Punch units (PU3100, PU3080), Unicode Font Package for SAP® 1 License, Color Controller E-26C, EFI Impose Type Digital, EFI Compose Type Digital, Hot Folders Type FS-100, Spot On Type FS100, Auto Trap Type FS-100, EFI CPS V5.X ES-3000 1 year Digital, EFI ES-3000, EFI Productivity Pack for Fiery E22b E22c

Consumables

Toner: black	31,000 prints
Toner: cyan/magenta/yellow	19,000 prints

Consumable yields based on 3 pages/job and 5% coverage on A4 paper

¹TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

- Some options may not be available at the time of market release.
- Specifications are subject to change without notice.
- For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.
- Some features may require additional options and/or charges.

This device does not support PoE (Power over Ethernet) and should not be connected to a PoE hub. Connecting to a PoE hub could cause damage and void warranty coverage.

RICOH
imagine. change.

Ricoh USA, Inc., 300 Eagleview Blvd, Exton, PA 19341, 1-800-63-RICOH

©2025 Ricoh USA, Inc. All rights reserved. Ricoh® and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.

R4175-2